

# 7100K-Series

High Density 10 Gigabit Ethernet Data Center Switch

## Benefits

### BUSINESS ALIGNMENT

- Standards-based Terabit architecture to support secure, reliable deployment of business-critical applications.
- Flexible, high speed connectivity support for 1,10, and 40 Gbps Ethernet to scale with growth in your data center.

### OPERATIONAL EFFICIENCY

- Integral element of Extreme Networks' OneFabric edge-to-edge network architecture reduces deployment and maintenance costs.
- High-density, small form system provides up to 64 wire speed 10Gb ports in a single rack unit, significantly reducing footprint costs.
- Management automation and built in resiliency reduce Total Cost of Ownership.
- Virtual Machine (VM) mobility tracking across multiple systems with dynamic policy.
- Automatically identifies and provisions devices and services, reducing IT deployment time.

### SECURITY

- Reduces risk and simplifies network administration with integrated security.
- MACsec link encryption for 10Gb ports

### SUPPORT AND SERVICE

- Industry leading customer satisfaction and first call resolution rates



Versatile high performance data center solution

Line rate 1.28 Tbps throughput with 952 Mpps packet forwarding

Automated network provisioning for the virtualized data center

Flexible connectivity options for 10 Gigabit and 40 Gigabit Ethernet

## Product Overview

The Extreme Networks 7100-Series is a family of high density, high-performance 10Gigabit Ethernet switches that are ideally suited for the demands of today's Enterprise data center. The 7100-Series is an ideal fit for support of high bandwidth and latency-sensitive applications.

The 7100-Series offers flexible connectivity options using modular SFP+ transceivers and Direct Attach Cables as well as integrated 10GBASE-T in both 24 and 48 access port configurations. Gigabit, 10 Gigabit, and 40 Gigabit ports are supported. Up to 64 line rate 10 Gigabit Ethernet ports can be supported in a in single rack unit configuration, maximizing the space available for servers and storage in dense data center Top of Rack (ToR) applications. Configurable air flow allows for adaptation to the specific hot-aisle / cold-aisle configuration of your data center.

The 7100-Series 10 Gigabit Ethernet switches are available in the following configurations:

- 7148 - 48 ports 1/10Gb SFP+ with 4 10/40Gb QSFP+ ports
- 7124 - 24 ports 1/10Gb SFP+ with 4 10/40Gb QSFP+ ports
- 7148T - 48 ports 1/10GBASE-T with 4 10/40Gb QSFP+ ports
- 7124T - 24 ports 1/10GBASE-T with 4 10/40Gb QSFP+ ports

All systems support redundant modular power supplies and fan modules and Extreme Networks Virtual Switch Bonding to configure highly available system configurations for mission critical data center environments.

The 7100-Series is an integral element of the Extreme Networks OneFabric network architecture. OneFabric is designed to help enterprises maintain an integrated end user experience while migrating towards a virtualized network environment.

Virtualization awareness addresses the need for visibility and awareness as virtual servers get deployed and adapt to Virtual Machine mobility. Data Center Bridging effectively supports the convergence of LAN I/O and storage traffic in the data center fabric. High performance virtual switching increases the available bandwidth in the data center and enables resilient network topologies to servers and aggregation switches. Higher aggregated capacity enables data centers to effectively scale with lower latency and higher levels of availability.

Management integration and automation enables a high degree of visibility and control of critical data center resources, providing a consistent edge-to-core

network implementation. Bandwidth and priority policies can be centrally provisioned, delivering a consistent implementation across the network.

## Features/Standards and Protocols

### SWITCHING/VLAN SERVICES

802.3ab Gigabit Ethernet (copper)  
802.3z Gigabit Ethernet (fiber)  
802.3ae 10 Gigabit Ethernet (fiber)  
802.3an 10GBASE-T (copper)  
802.3ba 40 Gigabit Ethernet  
802.1Q VLANs  
802.1D MAC Bridges  
802.1w Rapid re-convergence of Spanning Tree  
802.1s Multiple Spanning Tree - up to 16 instances  
802.1t - Path Cost Amendment to 802.1D  
802.1AX-2008 LACP

- 802.3ad Link Aggregation
- up to 64 groups with up to 8 ports in a group

Loop Protect  
802.3x Flow Control  
Jumbo Packet (9216 bytes)  
RFC 1191 Path MTU Discovery  
Link Flap Detection  
Dynamic Egress (Automated VLAN Port Configuration)  
IGMP v1/v2/v3  
IGMP snooping  
IGMP querier  
IPv6 Multicast Listener Discovery (MLDv1/v2)  
MLD snooping  
MLD querier  
GARP VLAN Registration Protocol (GVRP)  
802.1ak Multiple VLAN Registration Protocol (MVRP/MRP)  
Provider Bridges (IEEE 802.1ad) Ready

### DATA CENTER BRIDGING

802.1Qaz

- Enhanced Transmission Selection (ETS )
- Data Center Bridge Exchange Protocol (DCBx )
- Application Priority

802.1Qbb Priority Flow Control (PFC)  
802.1Qau Congestion Notification (CN)

### QOS

Strict Priority Queuing  
Weighted Round Robin  
8 Transmit Queues per Port  
ToS/DSCP Marking/Remarking  
802.1p - Class of Service  
802.1D Priority-to-Transmit Queue Mapping  
Ingress rate limiting  
Transmit queue shaping

### SECURITY

802.1X Port-based Authentication  
Port Web-based Authentication (PWA)  
MAC-based Authentication  
Extreme Networks dynamic policy  
Convergence Endpoint (CEP) Discovery with Dynamic Policy Mapping (Siemens HFA, Cisco VoIP, H.323, and SIP)  
Multiple Authentication Types per Port Simultaneously  
Multiple Authenticated users per Port with unique policies per user/End System (VLAN association independent)  
RFC 3580 IEEE 802.1 RADIUS Usage Guidelines, with VLAN to Policy Mapping  
Broadcast Suppression  
RADIUS snooping  
MAC-to-Port Locking - static and dynamic  
Span Guard (Spanning Tree Protection)  
Host CPU Denial of Service (DoS) protection  
MSCHAP RADIUS authentication  
IPsec RADIUS connection  
802.1AE MACsec link encryption (MACsec license)

### IPV4 / IPV6 ROUTING

Base System:  
IPv4/IPv6 Static Routing  
RIPv2  
RIPng  
VRRP  
IPv4 Policy Based Routing (PBR)  
DVMPRP

## ADVANCED L3 ROUTING LICENSE:

OSPFv2/v3

ISIS

PIM-SM

PIM-DM

PIM-SSM

BGP

Fabric Routing

VRF

## HIGH AVAILABILITY

Virtual Switch Bonding (VSB)

- Up to 8 systems in a VSB stack with 40Gb interconnects
- VSB mix of 7100K and 7100G systems
- VSB supported over any supported 40Gb media options
- When Advanced L3 functionality is required in a VSB stack, all 7100 systems in a VSB stack require an Advanced L3 license

High Availability Firmware Upgrade (HAU)

Redundant hot swappable fan modules

Redundant hot swappable power supplies

## EXTREME NETWORKS MANAGEMENT

NMS Console

NMS Policy Manager

NMS Inventory Manager

NMS Automated Security Manager

NMS NAC Manager

Data Center Manager (DCM)

## NETWORK MANAGEMENT

SNMP v1/v2c/v3

WebView Management Interface

Industry Common Command Line Interface

Configurable Login Banner

Dual IPv4/IPv6 Management Support

Multiple local user account management

Multiple Software Image Support with Revision Roll Back

Multi-configuration File Support

Editable Text-based Configuration File

COM Port Boot Prom and Image Download

Telnet Server and Client

Secure Shell (SSHv1/v2) Server and Client

Cabletron Discovery Protocol

Cisco Discovery Protocol v1/v2

802.1ab LLDP, LLDP-MED

802.3-2008 Clause 57 (Ethernet OAM - Link Layer OAM)

Port Mirroring - one to one, many to one, one to many

Unidirectional Link Detection (ULD)

Syslog

Audit Trail Logging

FTP/TFTP Client

Secure Copy Protocol (SCP)

RFC 2030 Simple Network Time Protocol (SNTP)

RFC 2865 RADIUS

RFC 2866 RADIUS Accounting

TACACS+

Management VLAN

RMON - Statistic, History, Alarms, Events

RFC 2613 SMON

DHCP server

Environmental Monitoring

## STANDARD MIB SUPPORT

RFC 1156/1213 & RFC 2011 IP-MIB

RFC 1493 Bridge MIB

RFC 1659 RS-232 MIB

RFC 2578 SNMPv2 SMI

RFC 2579 SNMPv2-TC

RFC 3417 SNMPv2-TM

RFC 3418 SNMPv2 MIB

RFC 2012 TCP MIB

RFC 2013 UDP MIB

RFC 3411 SNMP Framework MIB

RFC 3412 SNMP-MPD MIB

RFC 3413 SNMPv3 Applications

RFC 3414 SNMP User-Based SM MIB

RFC 2276 SNMP-Community MIB

RFC 2613 SMON MIB

RFC 2674 802.1p/q MIB

RFC 2737 Entity MIB

RFC 2819 RMON MIB (Groups 1-9)

RFC 3273 HC RMON MIB

RFC 2863 IF MIB

RFC 2864 IF Inverted Stack MIB

RFC 2922 Physical Topology MIB

RFC 3291 INET Address MIB

RFC 3415 SNMP View Based ACM MIB

RFC 3635 EtherLike MIB

RFC 3636 MAU MIB

RFC 4022 MIB for the Transmission Control Protocol (TCP)

RFC 4113 MIB for the User Datagram Protocol (UDP)

RFC 4293 MIB for Internet Protocol (IP)

IEEE 8023 LAG MIB

RSTP MIB

USM Target Tag MIB

U Bridge MIB

SNMP-REARCH MIB

IANA-address-family-numbers MIB

IEEE 802.1PAE MIB

## 7100-Series Switch Model Specifications

	7148	7124	7148T	7124T
<b>PERFORMANCE</b>				
Switching Throughput Mpps	952 Mpps	595 Mpps	952 Mpps	595 Mpps
Switching Capacity	1.28 Tbps	800 Gbps	1.28 Tbps	800 Gbps
Max 10Gb Ethernet Ports	64	40	64	40
Max 40Gb Ethernet ports	4	4	4	4
MAC Address Table	128K	128K	128K	128K
VLANs Supported	4,094	4,094	4,094	4,094
Packet Buffers	9MB	9MB	9MB	9MB
<b>PHYSICAL SPECIFICATION</b>				
Dimensions (H x W x D), Rack Units	<ul style="list-style-type: none"> <li>• 1 Rack Unit high</li> <li>• 4.37 cm H x 44.73cm W x 43.40cm D</li> <li>• 1.72" H x 17.61" W x 17.086" D</li> </ul>	<ul style="list-style-type: none"> <li>• 1 Rack Unit high</li> <li>• 4.37 cm H x 44.73cm W x 43.40cm D</li> <li>• 1.72" H x 17.61" W x 17.086" D</li> </ul>	<ul style="list-style-type: none"> <li>• 1 Rack Unit high</li> <li>• 4.37 cm H x 44.73cm W x 43.40cm D</li> <li>• 1.72" H x 17.61" W x 17.086" D</li> </ul>	<ul style="list-style-type: none"> <li>• 1 Rack Unit high</li> <li>• 4.37 cm H x 44.73cm W x 43.40cm D</li> <li>• 1.72" H x 17.61" W x 17.086" D</li> </ul>
Net Weight	7.12 kg (15.7 lb)	7.12 kg (15.7 lb)	7.12 kg (15.7 lb)	7.12 kg (15.7 lb)
Physical Ports	<ul style="list-style-type: none"> <li>• (48) 1Gb/10Gb SFP+ ports, MACsec capable</li> <li>• (4) 10Gb/40Gb QSFP+ ports</li> <li>• (1) Console port</li> <li>• (1) Micro-USB port</li> </ul>	<ul style="list-style-type: none"> <li>• (24) 1Gb/10Gb SFP+ ports, MACsec capable</li> <li>• (4) 10Gb/40Gb QSFP+ ports</li> <li>• (1) Console port</li> <li>• (1) Micro-USB port</li> </ul>	<ul style="list-style-type: none"> <li>• (48) 1Gb/10Gb 10GBASE-T ports, EEE and MACsec capable</li> <li>• (4) 10Gb/40Gb QSFP+ ports</li> <li>• (1) Console port</li> <li>• (1) Micro-USB port</li> </ul>	<ul style="list-style-type: none"> <li>• (24) 1Gb/10Gb 10GBASE-T ports, EEE and MACsec capable</li> <li>• (4) 10Gb/40Gb QSFP+ ports</li> <li>• (1) Console port</li> <li>• (1) Micro-USB port</li> </ul>
<b>POWER</b>				
Power Supplies	Up to two load sharing redundant 460 W power supplies	Up to two load sharing redundant 460 W power supplies	Up to two load sharing redundant 460 W power supplies	Up to two load sharing redundant 460 W power supplies
Normal Input Voltage	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC	100 - 240 VAC
Input Frequency	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz
Max Power Consumption	174 W	138 W	318 W	206 W
<b>ENVIRONMENTAL</b>				
Operating Temperature	5° to 40° C (41° to 104° F)	5° to 40° C (41° to 104° F)	5° to 40° C (41° to 104° F)	5° to 40° C (41° to 104° F)
Non-Operating Temperature	-30° to 73° C (-22° to 164° F)	-30° to 73° C (-22° to 164° F)	-30° to 73° C (-22° to 164° F)	-30° to 73° C (-22° to 164° F)
Operating Relative Humidity	5% to 95% (non-condensing)	5% to 95% (non-condensing)	5% to 95% (non-condensing)	5% to 95% (non-condensing)
<b>AGENCY SPECIFICATIONS</b>				
Safety	UL 60950-1, FDA 21 CFR 1040.10 and 1040.11, CAN/CSA C22.2, No. 60950-1, EN 60950-1, EN 60825-1, EN 60825-2, IEC 60950-1, 2006/95/EC (Low Voltage Directive)			
Electromagnetic Compatibility	FCC 47 CFR Part 15 (Class A), ICES-003 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, EN 61000-3-3, AS/NZ CISPR-22 (Class A), VCCI V-3, CNS 13438 (BSMI), 2004/108/EC (EMC Directive)			
Environmental	2002/95/EC (RoHS Directive), 2002/96/EC (WEEE Directive), Ministry of Information Order #39 (China RoHS)			

## Model Number Information

PART NUMBER	DESCRIPTION
<b>7100-SERIES SWITCHES</b>	
71K1L4-48	7148, 48 ports 1/10Gb SFP+ with 4 10/40Gb QSFP+ ports, includes 2 reversible fan modules and a two post rack mount kit. Power supplies ordered separately.
71K1L4-24	7124, 24 ports 1/10Gb SFP+ with 4 10/40Gb QSFP+ ports, includes 2 reversible fan modules and a two post rack mount kit. Power supplies ordered separately.
71K9L4-48	7148T, 48 ports 1/10GBASE-T and EEE with 4 10/40Gb QSFP+ ports, includes 2 reversible fan modules and a two post rack mount kit. Power supplies ordered separately.
71K9L4-24	7124T, 24 ports 1/10GBASE-T and EEE with 4 10/40Gb QSFP+ ports, includes 2 reversible fan modules and a two post rack mount kit. Power supplies ordered separately.
<b>POWER SUPPLIES</b>	
71A-PS-A	7100 Power Supply, 460W, 100-240VAC input, System I/O side air exhaust
71A-PS-B	7100 Power Supply, 460W, 100-240VAC input, System I/O side air intake
<b>OPTIONAL LICENSES</b>	
71A-EOS-ADVL3	7100K-Series (10Gb models) Advanced Routing License - OSPFv2, OSPFv3, ISIS, PIM-SM, PIM-DM, PIM-SSM, BGP, Fabric Routing, VRF
71A-EOS-KMACSEC	7100K-Series MACsec license to enable MACsec on MACsec capable ports
<b>SPARES AND ACCESSORIES</b>	
71A-FAN	7100 Fan Module, Spare. Reversible air flow.
71A-RACK-U	7100 Universal rack mount kit for four post rack mount options

### POWER CORDS

In support of its expanding Green initiatives as of July 1st 2014, Extreme Networks will no longer ship power cords with products. Power cords can be ordered separately but need to be specified at the time order. Please refer to [www.extremenetworks.com/product/powercords/](http://www.extremenetworks.com/product/powercords/) for details on power cord availability for this product.

See the Extreme Networks Pluggable Transceivers data sheet at <http://www.extremenetworks.com/products/transceivers-ds.pdf> for a full list of supported transceivers.

## Transceivers

Extreme Networks transceivers provide flexible connectivity options for Ethernet. All Extreme Networks transceivers meet the highest quality for extended life cycle and the best possible return on investment. For detailed specifications, compatibility and ordering information please go to: <http://www.extremenetworks.com/product/transceivers/>

## Service and Support

Extreme Networks provides comprehensive service offerings that range from Professional Services to design, deploy and optimize customer networks, customized technical training, to service and support tailored to individual customer needs. Please contact your Extreme Networks account executive for more information about Extreme Networks Service and Support.

## Warranty

The Extreme Networks 7100-Series comes with a one year hardware warranty. For full warranty terms and conditions please go to: <http://www.extremenetworks.com/support/policies#warrantyTag>



<http://www.extremenetworks.com/contact> / Phone +1-408-579-2800

©2015 Extreme Networks, Inc. All rights reserved. Extreme Networks and the Extreme Networks logo are trademarks or registered trademarks of Extreme Networks, Inc. in the United States and/or other countries. All other names are the property of their respective owners. For additional information on Extreme Networks Trademarks please see <http://www.extremenetworks.com/company/legal/trademarks>. Specifications and product availability are subject to change without notice. 6121-0915-01